

### ✓ Mesh Panel ST 30

ST 30 panels from Troax have a standard mesh aperture of 20x100mm, which allows for a safety distance of 120 mm. The horizontal wire is placed on the inside of the panel to enhance protection, as it makes climbing the panel virtually impossible. This design also facilitates excellent visibility through the mesh panel. Furthermore, our welding techniques in combination with our patented profile design give our panels superior strength. We can accommodate any requirement for machine safety applications.



#### FACTS

Art no	Width (mm)	Height (mm)	Weight (mm)
29020601	200	1200	3.1
29030601	300	1200	3.6
29070601	700	1200	6.2
29080601	800	1200	6.9
29100601	1000	1200	8.2
29120601	1200	1200	9.2
29150601	1500	1200	11.3
29020621	200	2000	4.9
29030621	300	2000	5.6
29070621	700	2000	9.3
29080621	800	2000	10.1
29100621	1000	2000	11.8
29120621	1200	2000	13.2
29150621	1500	2000	16.2

#### Frame dimensions:

Tube 30x20mm

#### Wire dimensions:

3,0mm vert.

3,0mm horizont.

#### Mesh size:

20x100mm

#### Standard colour:


Grey RAL 7037

Black RAL 9005

#### Other RAL colours or

#### Hot Dip Galvanized:

On customer's request



ST 30 mesh panels are also compatible with our Smart Fix and Safe Fix systems.

#### ACCESSORIES

29500221 Snapper 3020

29500700 Rubber profile (Black)

29600161 Tube 30x20x1200 mm

29600181 Tube 30x20x2000 mm