

### ✓ Mesh Panel ST 30

ST 30 panels from Troax have a standard mesh aperture of 20x100mm, which allows for a safety distance of 120mm. The horizontal wire is placed on the inside of the panel to enhance protection, as it makes climbing the panel virtually impossible. This design also facilitates excellent visibility through the mesh panel. Furthermore, our welding techniques in combination with our patented profile design give our panels superior strength. We can accommodate any requirement for machine safety applications.



#### FACTS

| Art no   | Width (mm) | Height (mm) | Weight (kg) |
|----------|------------|-------------|-------------|
| 29020601 | 200        | 1200        | 3.1         |
| 29030601 | 300        | 1200        | 3.6         |
| 29070601 | 700        | 1200        | 6.2         |
| 29080601 | 800        | 1200        | 6.9         |
| 29100601 | 1000       | 1200        | 8.2         |
| 29120601 | 1200       | 1200        | 9.2         |
| 29150601 | 1500       | 1200        | 11.3        |
| 29020621 | 200        | 2000        | 4.9         |
| 29030621 | 300        | 2000        | 5.6         |
| 29070621 | 700        | 2000        | 9.3         |
| 29080621 | 800        | 2000        | 10.1        |
| 29100621 | 1000       | 2000        | 11.8        |
| 29120621 | 1200       | 2000        | 13.2        |
| 29150621 | 1500       | 2000        | 16.2        |

#### Frame dimensions:

Tube 30x20mm

#### Wire dimensions:

3,0mm vert.

3,0mm horizont.

#### Mesh size:

20x100mm

#### Standard colour:


Grey RAL 7037

Black RAL 9005

#### Other RAL colours or

#### Hot Dip Galvanized:

On customer's request



Smart Fix mesh panels are also compatible with our Rapid Fix and Safe Fix systems.

#### ACCESSORIES

29500221 Snapper 3020

29500700 Rubber profile (Black)

26700049 Bracket for corner (SF)

36700079 Bracket for corner (SmF)

29600161 Tube 30x20x1200 mm

29600181 Tube 30x20x2000 mm