

✓ Mesh Panel UX 550

UX 550 is the most heavy-duty of our panel systems. Special profiles are used for installation to prevent even the slightest chance of prying the wall sections apart. The system is tested and approved in-line with pre-standard EN1627-30. Troax UX 550 is primarily used as a front wall where extra security is needed. UX 550 is compatible with UR 350 and UX 450 for inner walls. Troax modular mesh panel system makes it possible to create separate storage areas in virtually any common space. The 50x50 mesh aperture also makes it virtually impossible for a hand to reach through the panel.



FACTS

Art no	Width (mm)	Height (mm)	Weight (kg)
36020101	200	2200	7.49
36030101	300	2200	9.15
36070101	700	2200	15.58
36080101	800	2200	17.2
36100101	1000	2200	20.44
36120101	1200	2200	23.67
36150101	1500	2200	28.53

The Mesh Panels above can be customised with doors, tubes and shelves to suit your application. Contact your local sales office for more information.

Frame dimensions:

30x20x1,5mm vert.
30x20x1,25mm horizont.

Wire dimensions:

5,0x5,0mm

Mesh size:


50x50mm

Standard RAL colour:

Grey RAL 7037

Other RAL colours or Hot Dip Galvanized:

On customer's request



ACCESSORIES

36700023, Roof fixing L=600mm
36700025, Roof fixing L=1000mm
36500511, Single profile UX 550 L=2160mm
36500521, Join profile UX 550 L=2160mm
36500531, Corner profile UX 550 L=2160mm outwards
36500541, Corner profile UX 550 L=2160mm inwards
36500550, Wall profile UX 550 L=2160mm
36500561, Join profile UX 550 L=2160mm

35700119, 2-hole bracket Kit (10pcs)
35700219, 3-hole bracket Kit (10pcs)
35700219, 2-hole angle Kit (10pcs)
35700239, 3-hole angle Kit (10pcs)
35700259, 5-hole angle Kit (10pcs)
35700269, 9-hole angle Kit (10pcs)
89300045, Hilti Nail-plug HPS 15/5x35mm
20500320, Drill Quick 4,8x13 (100pcs)
Door UX 550 (see separate product sheet)